



PUSH BUTTONS

Indicator Light/Push Button Push-To-Test Operators

Class I, Groups C & D
Class II, Groups E, F & G
NEMA 7 & 9



XLP Long Series
(Long Barrel)



XLPS Short Series
(Short Barrel)

STANDARD FEATURES

- Die cast aluminum alloy. The barrels are all $\frac{3}{4}$ " NPSM thread. Maximum installation thickness 1 $\frac{15}{16}$ " Long Barrel, $\frac{3}{4}$ " Short Barrel.
- Furnished standard with 120 volt slide base lamp. Also available for 6, 12, 24, 28, 48 and 60 volts. Specify when ordering.
- For use with BT contact blocks. Contact blocks can be stacked for multiple circuits. Contact blocks are not included with the operators. For NEMA 4 application, add boot and special legend plate. (See accessories at end of section)


LONG BARREL

Catalog #	Operator Description	Weight (lbs.)
XLPA	Amber Lens	$\frac{3}{4}$
XLPB	Blue Lens	$\frac{3}{4}$
XLPC	Clear Lens	$\frac{3}{4}$
XLPG	Green Lens	$\frac{3}{4}$
XLPR	Red Lens	$\frac{3}{4}$
XLPW	White Lens	$\frac{3}{4}$

SHORT BARREL

Catalog #	Operator Description	Weight (lbs.)
XLPAS	Amber Lens	$\frac{1}{2}$
XLPBS	Blue Lens	$\frac{1}{2}$
XLPCS	Clear Lens	$\frac{1}{2}$
XLPGS	Green Lens	$\frac{1}{2}$
XLPRS	Red Lens	$\frac{1}{2}$
XLPWS	White Lens	$\frac{1}{2}$

LEGEND PLATES AT END OF SECTION



XLT

Pilot Light Transformers

One transformer required for each pilot light. Adapter furnished for mounting on threaded pilot light stem, or can be mounted to housing as space requires.

PILOT LIGHT TRANSFORMERS

Catalog #	Description	Weight (lbs.)
XLT 240	240 to 120 Volt, 6VA	1